

EVOTEC



Fume and Dust Extraction FEX 3000 VA



[Discover now](#)



**INNOVATIVE
EXTRACTION TECHNOLOGY**



Mobile fume extraction FEX 3000 VA

EVOTEC



- Process-adaptable extraction system for extracting fume, fumes, or airborne dust
- Powerful EC blowers suitable for continuous operation (24/7), large air volume, stepless volume flow control
- Modern control technology with device status display and filter notifications
- Reliable filtration through a graduated combination filter system
- Connection for on/off remote control
- **Stainless steel housing (VA 1.4301)**

Versions:



Process-adaptable extraction system for extracting fume, soldering fumes, vapors, or airborne dust

High quality standards – suitable for **3-shift operation**.

Convenient filter replacement through **3-cassette system** with independently replaceable filter cassettes.

Reliable filtration of airborne particles by using a 3-stage combination filter system. The activated carbon filter reduces odors in the exhaust air. **For extraction of laser fume, welding and soldering fumes, cutting fume as well as various vapors and solvents.**

EC fans suitable for continuous operation for extracting large air volumes to capture airborne dust.

Extraction with up to two hoses or extraction arm, hose connection at the rear or on top.

Easily and conveniently adaptable to individual requirements via **intuitive control panel**.

Clear graphic display and large, multi-colored LEDs for a quick **overview of device status** or settings.

ESD and EX protection ATEX Zone 22

Device equipment and device parts are electrostatically dissipative for safe extraction in Zone 22. Initial filter equipment set (with grounding lug) consisting of:

- Expanded metal filter
- Storage filter with F9 + M5 insert
- HEPA filter H13/H14
- Activated carbon filter

W3 version – IFA-tested incl. expanded metal filter as spark arrestor to prevent fire hazard. Initial filter equipment set consisting of:

- Expanded metal filter
- Storage filter with F9 + M5 insert
- HEPA filter H13/H14
- Activated carbon filter


Model		FEX 3000 VA
Voltage at 50/60 Hz.	Volt	230 (or 110)
Motor power	Watt	1.100
Maximum air volume in operating condition *)	m³/h	260
1st filter stage storage filter frame F9 + M5	m²	2,5 + 0,8
2nd filter stage: HEPA filter H13/H14	m²	5,6
3rd filter stage: AK adsorption filter	kg	6,0
Max. air volume <i>turbine output at free outlet</i>	m³/h	460
Maximum negative pressure <i>at the closed suction nozzle</i>	Pa	10.000
Sound pressure level	dB(A)	62
Weight	kg	25 (+20 filter)
Dimensions L x W x H	mm	430 x 400 x 1060
Protection class		IP 55
Operating temperature	°C	5 - 40
Operating humidity (non-condensing)	%	10 - 90
Housing		Stainless steel VA 1.4301
ESD and EX-protected (electrostatically dissipative)	Art. No.	710-1131
W3 version (welding fumes)	Art. No.	710-1132

*) **Operating data** including standard filter equipment in factory condition without further options such as Activated carbon filter, spark trap, piping, etc. The effective performance depends on the respective operating point, which is determined by power setting, pipe dimension (Ø, length), and capture at the suction point.

**) For recirculation operation, country-specific requirements must be checked.

FEX 3000 VA

EVOTEC



High-performance extraction technology requires optimally matched control systems. For this reason, our FEX series is equipped with a **configurable control unit** that can be **precisely adapted** to your extraction process. Operation is carried out via a **clear and intuitive control panel**.

- A test routine for the motor, buttons, LEDs and more ensures comprehensive functionality for maximum safety.
- A wide range of fault notifications and filter status messages – displayed with pictograms and error codes.
- Error logging for traceability – enabling the best possible service.
- Filter fill level displayed in real time – individually for each filter.
- Different user roles with varying permission levels and individual passwords.
- Real-time fill level display, individually adjustable to your conveyed material – for maximum accuracy.
- Individually adjustable run-on time to ensure the highest possible extraction rate.
- Alarm configuration according to the relevance within your extraction process.


Connection for remote ON/OFF control (remote control).

Connection to external controllers or devices:
8-pin connector socket enabling remote ON/OFF switching. Operating status and fault signals can be transmitted either potential-free or with 24 V.

The matching mating connector is available as an accessory.

Upgrade (072-0618): Gas- and Particle Sensor

- Detects filter breakthrough and can initiate immediate shut-down if required.
- Sensitivity configurable in the user menu (sensor service life: 1 year).
- Test function to ensure reliable functionality.




[Learn more](#) 

Replacement filters for FEX 3000

EVOTEC

HEPA filter and adsorption filter consist of a sturdy MDF-box with sealing and are fully incinerable. Due to the separate variant, the filters can be combined depending on the application and be disposed separately depending on the filter load.

As storage filter, different variants can be chosen: ready-to-use combi filter cassette F9/M5 or diverse system frames, which can be equipped with different filter insets depending on the application.



Filter technology

Three independently replaceable cassette filters MDF frame, completely incinerable

Filter stage 1, storage filter: M5/F9 combination of synthetic pleat and glass fiber fleece, filter area 1.2 m² / 5.0 m²

Optionally, the storage filter can be supplemented with replaceable exchange inserts in various filter qualities.

Filter stage 2, suspended matter filter: HEPA H13/14, filter area 5.6 m²


Filter stage 3, adsorption filter: activated carbon filling 5.8 kg

Available for welding fume extraction: expanded metal filter as spark protection.


The filters used correspond at least to the dust class indicated on the outside of the device. **This must be observed when changing the filter.**

User-friendly, low-contamination filter change. The cover cardboard and insert cardboard supplied with the replacement filter prevent contamination inside the device.

For easy filter replacement, a replacement kit consisting of: filter cover cardboard, disposal bag, dust mask, and disposable gloves is available separately



Hoses and connections FEX

	Suction hose PUR black antistatic volume and surface resistance < 10⁹ ohms per running meter Ø 50 mm 072-10007 End sleeve electrically conductive for PUR suction hose, 1 piece Ø 50 mm 072-10025 
	Suction hose PP for W3 version per running meter (not suitable for EX) Ø 50 mm 072-10003 End sleeve for PP suction hose, 1 piece Ø 50 mm 072-10001
	Secondary suction connection kit Cover plate with 2 holes of Ø 50 mm each, gasket, sealing plug, for connecting additional suction hoses 2 x Ø 50 mm 072-0607
	Sealing plug for sealing unused suction openings Ø 50 mm 072-0609

Hoses and connections FEX

	Adapter for suction hose connection For mounting on the housing cover, incl. hose clamp (Lindab) Ø 80 mm 072-0656 
	Exhaust or extraction hose PUR black antistatic Can be used as exhaust or extraction hose, volume and surface resistance < 10⁹ ohms per running meter Ø 80 mm 072-10011 Ø 100 mm 072-10035 
	Exhaust hood with exhaust hose connection Exhaust device cover with connection for exhaust hose (Lindab) Ø 80 mm 072-0655 
	Wire clamps individually For extraction or exhaust hoses, galvanized steel Ø 50 mm 054-10090 Ø 80 mm 054-10091 Ø 100 mm 054-10092 

Options FEX

	Spark trap with metal mesh insert prevents the intake of sparks. For integration into pipe system or suction hose. Ø 50 mm 072-0626 Ø 80 mm 0720628 Matching metal mesh insert for Ø 50 mm 072-0626-01 Ø 80 mm 072-0628-01
	Holder for spark trap included in delivery. For variable mounting of the spark trap at any angle on supports.
	Expanded metal filter as spark arrestor to prevent fire hazard, suitable for storage filter Piece 074-20058
	Cyclone pre-separator ESD for pre-separation of larger amounts of fine dust. 28-liter dirt container with cyclone made of ESD plastic. Connections Ø 50 mm Piece 053-1045

Options FEX

	Triangular socket key for front door Piece 074-20016
	Power connection cable with angled cold appliance plug, 5 meters with EU-Schuko plug 072-0343 with open end 072-0130

Options FEX

	Counter plug for 8-pin socket for connection to external controllers or devices for remote control, without cable Piece 072-0621
	Gas and particle sensor as a supporting monitoring unit for damaged filters or saturated activated carbon. Suitable for gases: carbon monoxide, ammonia, sulfur dioxide, alcohol, gasoline. Attention: The unit must be ordered together with the machine. Sensor lifespan: 1 year Board unit 072-0618
	Test aerosol Test spray for functional testing of gas and particle sensor Can 072-0625
	Protective coating in the upper housing area, recommended for the extraction of acid-containing vapors Attention: Must be ordered together with the machine FEX 1000.1 072-0619-01 FEX 3000/ .1/ .2/ VA 072-0619-02 FEX 5000/ PRO 072-0619-03

Extraction arms





Extraction arms enable **point extraction** directly at the source. Thanks to **self-supporting construction** with three stable joints, easy to handle and easy to position.

Standard version: Aluminum with polypropylene joints
ESD version: for ESD areas (electrostatic discharge, certified according to IEC 61340-5-1).
Ideal for use in laboratories, electronics manufacturing, pharmaceutical industry, etc.





+ Energy-saving + Low noise + Low pressure loss

	Extraction arm for table mounting Including bracket for plate feed-through Illustration: Standard version Ø 50 mm – Range 1,300 mm Option: hood tube and flat hood
	Extraction arm for ceiling or wall mounting without bracket Illustration: ESD/ATEX version Ø 50 mm – Range 1,300 mm Option: hood tube and flat hood Option: small wall bracket

Extraction arms and brackets

	Extraction arm <u>Standard</u> for table mounting Including bracket for plate feed-through Ø 50 mm Range 1,300 mm 072-0400 Range 1,500 mm 072-0401 Ø 75 mm Range 1,300 mm 072-0402 Range 1,500 mm 072-0403
	Extraction arm <u>ESD</u> for table mounting Including bracket for plate feed-through Ø 50 mm Range 1,300 mm 072-0400-ESD Range 1,500 mm 072-0401-ESD Ø 75 mm Range 1,300 mm 072-0402-ESD Range 1,500 mm 072-0403-ESD
	Extraction arm <u>Standard</u> for ceiling or wall mounting, without bracket Ø 50 mm Range 1,300 mm 072-0404 Range 1,500 mm 072-0405 Ø 75 mm Range 1,300 mm 072-0406 Range 1,500 mm 072-0407
	Extraction arm <u>ESD</u>, for ceiling or wall mounting, without bracket Ø 50 mm Range 1,300 mm 072-0404-ESD Range 1,500 mm 072-0405-ESD Ø 75 mm Range 1,300 mm 072-0406-ESD Range 1,500 mm 072-0407-ESD



Extraction arms and brackets

	Flexible extraction arm <u>ESD</u> for table mounting Including bracket for plate feed-through Ø 50 mm Range 600 mm 072-0400-ESD
	Flexible table bracket Flexible holder for mounting on table tops or shelves. Supplied complete with two screw clamps. Suitable for 072-0400-ESD: 072-0409-ESD Universal for Ø 50 mm and Ø 75 mm standard 072-0428 ESD 072-428-ESD
	Wall bracket Universal holder/bracket for extraction arm for wall mounting. Suitable for Ø 50 mm and Ø 75 mm Standard 072-0427 ESD 072-0427-ESD
	Ceiling bracket Bracket also serves as an exhaust duct. Universally suitable for Ø 50 mm and Ø 75 mm Standard, length 250 mm 072-0418 ESD, length 250 mm 072-0418-ESD Standard, length 1,000 mm 072-0421 ESD, length 1,000 mm 072-0421-ESD → Further versions/lengths on request

Hoods and nozzles

	Flat hood 300 x 200 mm Especially suitable for gases and vapors. High extraction efficiency in a vertical position to the table surface, including hood pipe Standard Ø 50 mm 072-0414 ESD Ø 50 mm 072-0414-ESD Standard Ø 75 mm 072-0415 ESD Ø 75 mm 072-0415-ESD
	Suction tip, length 300 mm For smaller, concentrated pollutant sources. Overhang of the suction tip for increased extraction efficiency Standard Ø 50 mm 072-0410 ESD Ø 50 mm 072-0410-ESD Standard Ø 75 mm 072-0411 ESD Ø 75 mm 072-0411-ESD
	Flexible suction tip, length 600 mm, ESD High efficiency combined with high flexibility. ESD Ø 50 mm 072-0412 ESD Ø 75 mm 072-0413
	Round hood Metal hood Ø 250 mm, including hood pipe Standard Ø 50 mm 072-0432 ESD Ø 50 mm 072-0432-ESD Standard Ø 75 mm 072-0433 ESD Ø 75 mm 072-0433-ESD

Extraction arm accessories

	Ceiling bracket, telescopic up to a length of 1,000 mm Bracket also serves as an exhaust duct. Universally suitable for Ø 50 mm and Ø 75 mm Standard 072-0426 ESD 072-0426-ESD
	Straight hood pipe Spare part for hood, but also suitable as a straight inlet nozzle Standard Ø 50 mm 072-0429 ESD Ø 50 mm 072-0429-ESD Standard Ø 75 mm 072-0430 ESD Ø 75 mm 072-0430-ESD
	Reducer Material PP Standard Ø 100-50 mm 072-0416 ESD Ø 100-50 mm 072-0416-ESD Standard Ø 100-75 mm 072-0417 ESD Ø 100-75 mm 072-0417-ESD
	Protective grid For installation in Ø 75 mm joint Standard Ø 75 mm 072-0431 ESD Ø 75 mm 072-0431-ESD